4-688

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

MINERAL SURVEY NO. 4530

	Arizona I	and District.	
	FIELD NOTES		
	FIELD NOTES Of The Survey Of The Mining CI ROY CORNETT	laim Of	JAN 26 8
	ROY CORNETT		
	Known As The		<mark>.</mark> В
	up #1, New Group #2, New Group #3 and New Cherry C		
	Yavapai County,		
Section	30 and 31 , Township 11 N.	, Range 3 E	
Sur	veyed under order dated June 1 Amd. Dec. 1	, 1960 1960	
	by J. WILLIA	M WAARA Mineral S	Surveyor.
	ClaimslocatedDecember 20	1933.	
	Survey commenced June 20	, 1960	
	Survey completedJanuary 6	, 1961	
	Address of claimant Roy Cornett, Box 23	6, Congress, Ar	rizona
	DATES OF AMENDED LOCATION All lodes amended 12-19-60		

SETATE LEVELU. SECURITURE DET EN THERET RASCO

DOMESTIC BELLEVISION

STRIK GOTT

Assembly sound and 26 years Sould be

BRITISH OFFICE TO THE OWN

First Day

Chartes

This survey was made with a Lietz Light Mountain transit No. 9503 with horizontal limb five inches in diameter, having two double opposite verniers reading to thirty seconds of arc, and full vertical circle five inches in diameter, having double opposite verniers reading to one minute of arc, the eyepiece is equipped to receive a prismatic eyepiece with colored shade for direct observations on the sun. The instrument was in good condition at the time of the survey and all adjustments were in good order.

All azimuths in this record were determined by the method of deflection angles referred to the meridian established by direct observations on the sun, June 29, 1960 at Cor. No. 4, New Group #1 lode, latitude 34° 30' N., longitude 112° 04' 30" W., turning from a reference point southeast clockwise to the sun in the northwest.

True bearing of the reference point 'S. 89° 51' E.

The lines were measured with a steel tape, 1/8 in. wide, 500 feet long, graduated every foot. This tape was compared with a standard steel tape, 100 ft. long, at the time of the beginning of the survey and found correct.

All lines and connections of this survey were run by direct methods.

The magnetic declination observed at each corner of the survey gave a uniform value of ll_i ° 30' E.

SURVEY NO. 4530

New Group #1 lode

At Cor. No. 1 of the New Group #1 lode, identical with Cor. No. 3, Sur. No. 1555, Pittman lode.

Set a pipe, 36 ins. long, $\frac{1}{2}$ in. diam., 18 ins. in the ground, surrounded by a substantial amount of stone, fitted with a three-inch floor flange with copper plate bolted thereon, marked N G 1 1 4530 with its center for exact cor. point; from which

The cor: to Secs. 30 and 31 on the W. bdy. of T. 14 N., R. 3 E., Gila and Salt River Meridian, bears N. 88° 11' W., 742.1 ft. dist.

No other bearings available. des description and about

Thence N. 9° 29' E.

At Nor. In. 1 of the New Croup #2 Lode.

6.154

1473.33 Intersect line 1.1, Sur. No. 1555, Pittman lode, at a point from which Cor. No. 4 bears S. 78° 30' E., 48.05 ft. dist.

1513.45 | Cor. No. 2.

bruor

This corner point falls on a well traveled road where it was impracticable to establish a permanent monument; from which

The bearing rock for Cor. No. 4, Sur. No. 1555, Pittman lode, bears N. 12° 26' E., 76.32 ft. dist.

Feet	Corros Pert
ON THE	ord and the the second over drift for the second of the second over the second
32.8	Witness cor. to Cor. No. 2 Door are in the distance of the bound of th
of begin, obser- At the	surrounded by a substantial round of stone fitted with a three
160.0	Lode line, built a substantial mound of stone; discovery cut and shaft bears S. 5° 23' W., 950.0 ft.
460.0	Lode, detitude 14° 30' M. Longitude 112° 01' . sol cor. sol
	On line 2-3, New Group #4 lode of this survey.
de, 500 no a ning of	inch floor flange with compar plate helted thereon marked N.C.
direct	No bearings available.
	Thence S. 5° 23' W.
729.2	Road, bears SE to NW. To mits niles be the province and
1377.2	Cor. No. 2, New Group-#4 lode, identical with-Cor. No. 4, New Group #3 lode, both of this survey.
1500.0	Cor. No. 4
. 10. 3,	Set an iron pipe, 36 ins. long, $\frac{1}{2}$ in. diam., 18 ins. in the ground, surrounded by a substantial mound of stone, fitted with a three inch floor flange with copper plate bolted thereon, marked N G 1-4-4530 with its center for exact cor. point.
hnd, threu-	No bearings available.
I I O W	Thence N. 89 51 W. William Wich
120.0	Cor. No. 2, New Group #2 lode of this survey.
300.0	Lode line, built a substantial mound of stone; discovery cut and shaft bears N. 5° 23' E., 550.0 ft.
424.3	Lode line monument, New Group #2 lode of this survey.
568.5	Cor. No. 1, and place of beginning.
mori j	New Group #2 lode
	At Cor. No. 1 of the New Group #2 lode.
THE PERSON NAMED IN COLUMN TWO IS NOT THE OWNER.	Set an iron pipe, 36 ins. long, 2 in. diam., 18 ins. in the ground,
	surrounded by a substantial mound of stone, fitted with a three inch floor flange with copper plate bolted thereon, marked N G 2-1-4530 with its center for exact cor. point; from which

Feet	
Bowlese of	No other hearings available
3-1-130 sec-men	
	W G i-1 with this center for easet cor. point: from which
160.1	Cor. No. 3, Sur. No. 1555, Pittman lode, identical with Cor. No. 1, New Group #1 lode of this survey.
304.3	Lode line, built a substantial mound of stone; discovery shaft bears S. 9° 48' E., 360 ft. dist.
428.6	Lode line monument, New Group #1 lode of this survey.
608.6	Cor. No. 2
	On line 4-1, New Group #1 lode of this survey.
nerej	Set an iron pipe, 36 ins. long, ½ in. diam., 18 ins. in the ground, surrounded by a substantial mound of stone, fitted with a three inch floor flange with copper plate bolted thereon, marked N G 2-2-4530 with its center for exact cor. point.
	No bearings available
	Thence S. 9° 48' E.
500.73	Intersect line 3-4, New Group #3 lode of this survey.
1441.79	Intersect line 2-3, New Group #3 lode of this survey.
1500.0	378. Intersect line 9-3, New Grand #2 Lode of Duke Core No. 3.
earrid	Set an iron pipe, 36 ins. long, $\frac{1}{2}$ in. diam., 18 ins. in the ground, surrounded by a substantial mound of stone, fitted with a three inch floor flange with copper plate bolted thereon, marked N G 2-3-1530 with its center for exact cor. point.
	No bearings available
	Thence N. 89° 51' W.
304•3	Lode line, built a substantial mound of stone; discovery shaft bears N. 9° 48' W., 1140 ft. dist.
608.6	Cor. No. 4
	Set a pipe, 36 ins. long, ½ in. diam., 18 ins. in the ground, surrounded by a substantial mound of stone, fitted with a three inch floor flange with copper plate bolted thereon, marked N G 3-4-4530 with its center for cor. point.
	surreconded by a substantial mound of the test in the surrection of the surrection o
	Thence N. 9° 48' W.
1500.0	Cor. No. 1, and place of beginning.
erned Le	301.6 Low From #3 lode and the severy car and tunion . 108
te bruom	At Cor. No. 1 of the New Group #3 lode, identical with Cor. No. 1, New Group #4 lode of this survey.
	603.2 Cor. No. 1, and place of beginning.

But

	Survey No. 4530
CKKKs Feet	
	Set an iron pipe, 36 ins. long, ½ in. diam., 18 ins. in the ground, surrounded by a substantial mound of stone, fitted with three-inch floor flange with copper plate bolted thereon, marked N G 3-1-4530, N G 4-1 with its center for exact cor. point; from which
	The S. ½ sec. cor. of Sec. 30, T. 14 N., R. 3 E., bears N. 87° 25' E., 592.4 ft. dist.
fied	No other bearings available. 360.3 100 cores
	.verture mint to shof Thence S. 3° 57! W. mom said shoft d.854
995.0	Road, bears N. to S.
1500.0	Cor. No. 2. variate minis to offel fit quotal well all antif and
e ground, three N S	
	No bearings availableofdefisys empires of
	Thence N. 78° 09' W.
302.8	Lode line, built a substantial mound of stone; discovery cut and tunnel bears N. 4° 00' E., 530 ft. dist.
378.4	Intersect line 2-3, New Group #2 lode of this survey.
605.6	Cor. No. 3.
he ground, three N G	Set an iron pipe, 36 ins. long, $\frac{1}{2}$ in. diam., 18 ins. in the ground, surrounded by a substantial mound of stone, fitted with a three inch floor flange with copper plate bolted thereon, marked N G 3-3-4530 with its center for exact cor. point.
	No bearings available.
	Thence N. 4° 02' E.
882.87	Intersect line 2-3, New Group #2 lode of this survey.
1377.70	Cor. Ye. A of the Mentine w #1 lade of the advice acc 2.800
three	Cor. No. 4, identical with Cor. No. 2, New Group #4 lode and on line 3-4, New Group #1 lode, both of this survey.
D. W.	Set an iron pipe, 36 ins, long, $\frac{1}{2}$ in. diam., 18 ins. in the ground, surrounded by a substantial mound of stone, fitted with a three inch floor flange with copper plate bolted thereon, marked N G 3-4, N G 4-2-4530 with its center for exact cor. point.
	No bearings available
	Thence S. 78° 09' E.
301.6	Lode line, point falls in the road; discovery cut and tunnel bears S. 4° 00' W., 970.0 ft. dist.
320.6	Witness monument to lode line point, built a substantial mound of stones.
603.2	Cor. No. 1, and place of beginning.

particely Mo. 11230	Survey	No.	4530
---------------------	--------	-----	------

100		. But vey No. 4230	
	Feet	New Group #14 lode	Special Control
CC	of Local Section of the Communication of the Commun	Beginning at Cor. No. 1 of the New Group #4 lode, identic Cor. No. 1, New Group #3 lode, of this survey.	al with
		Thence N. 78° 09' W.	
	282.6	Lode line witness monument.	
	301.6	Lode line point; discovery shaft bears N. 5° 23' E., 1490	0.0 ft.
	603.2	Cor. No. 2, identical with Cor. No. 4, New Group #3 loc survey, on line 3-4, New Group #1 lode of this survey.	le of this
		Thence N. 5° 23' E.	
		Road, bears NW to SE.	1 .01
	.13.036	Cor. No. 3. New Group #2 lode of this survey.	
	j: same	Cor. No. 3. has a martiled and their rillies to the standard and the stand	
	to roofi	Set an iron pipe, 36 ins. long, $\frac{1}{2}$ in. diam., 18 ins. in t surrounded by a substantial mound of stone, fitted with a inch floor flange with copper plate bolted thereon, marked 4-3-4530 with its center for exact cor., point.	three
		No bearings available.	
H	100 995	Thence S. 78° C9' E. The A	Wo. 2
	301.6	Lode line, built a substantial mound of stone; discovery bears S. 5° 23' W., 10.0 ft.	
	603.2	The Hardwary shaft of the Congress of the Cong	
	from the	Set an iron pipe, 36 ins. long, $\frac{1}{2}$ in. diam., 18 ins. in t surrounded by a substantial mound of stone, fitted with a floor flange with copper plate bolted thereon, marked N G with its center for exact cor. point.	he ground, three inch
		No bearings available.	
	45 3 FEB	Thence S. 5° 23' W.	10.3
	1500.0	Cor. No. 1, and place of beginning.	
		AREAS	Acres
5	n Cor. No erly, usv	Total area, New Group #1 lode Area in conflict with	17.632
		Sur. No. 1555, Pittman lode	0.812
7	n dor be chleanter	· Total area, New Group #2 lode Area in conflict with	26.642
		New Group #3 lode of this survey	2.280
10	Latrog of	Total area, New Group #3 lode	20.617
	ODreid 1	Total area, New Group #4 lode	20.639

CETS-N

Feet

DAGE WARRED LOCATION

This survey is located in the SW \(\frac{1}{4} \) of Sec. 30 and NW \(\frac{1}{4} \) of Sec. 31, T. 1\(\text{N.}, R. 3 \) E., Gila and Salt River Meridian, Prescott National Forest, Cherry Creek Mining District, Yavapai County, State of Arizona.

The survey of these lodes is identical with their respective locations, as marked upon the ground.

. TO O THE CONTROL OF THE STREET OF THE STRE

The improvements and the value of the labor and improvements made upon or for the benefit of the lode locations embraced in said mining claim by the claimant or his grantors are as follows:

No. 1 The discovery cuts and shafts of the New Group #1 lode, the center of the entrance cut being the discovery point is on the lode line N. 5° 23' E., 550 ft. from its intersection with line 4-1, 300 ft. from Cor. No. 4, this improvement being a cut running easterly 45 ft. to its mouth, and westerly 5.0 ft. to its face to intersect a concreted collar shaft on the latter's east wall, shaft being 4x6x6 caved, from north wall of the shaft extends a cut northerly 6x50x15 foot face, at the face is located a shaft in the floor of the cut, 4x6x24 ft. deep.

Value cut, \$250.

Value shaft, 150.

Value cut, 450.

Value cut, 450. Value shaft, 400.

No. 2 A shaft with concrete collar, the center of which bears N. 27° 30' E. 780 ft. from Cor. No. 1, New Group #1 lode, 4x6x22 ft. deep. Value, \$400.

. oldslisvo . I into g

W. bearings availand of

- No. 1 The discovery shaft of the New Group #2 lode, the center of which being on the lode line S. 9° 48' E., 360 ft. from the center of line 1-2, 4x6x8 ft. deep, caved.

 Value, \$100.
- No. 2 A shaft, the center of which bears S. 9° 48' E., 260 ft. from the North Center end, New Group #2 lode, 8x6x5 ft. deep, caved, in cut 8x10x6 foot face bears southerly.

Value cut, \$80. Value shaft, 80.

No. 3 A cut and tunnel, the face of the cut bears S. 9° 48' E., 215 ft. from North Center End, New Group #2 lode, cut 4x30x10 foot face, tunnel 4x6x15, caved, bears southerly.

Value cut, \$200. Value tunnel, 200.

- No. 4 A cut, the face of which bears S. 49° 30' E., 245 ft. from Cor. No.1, New Group #2 lode, cut 4x20x10 foot face, bears southeasterly, caved. Value, \$150.
- No. 5 A cut, the face of which bears S. 42° 00' E., 328 ft. from Cor. No.1, New Group #2 lode, cut 4x20x10 foot face, caved, bears southeasterly. Value, \$150.
- No. 1 The discovery cut and tunnel of the New Group #3 lode, the portal of tunnel being the discovery, is on the lode line N. 4° 00' E., 530 ft. from the center of line 2-3, cut 5x20x10 foot face, tunnel 4x6x30 ft. caved, bears northerly, with pit easterly from mouth of cut, pit 40x70x6 to 8 foot face.

Survey No. 4530 8 Chains OTHER IMPROVEMENTS None, Houses heretofore destroyed by fire. • OTHER CORNER DESCRIPTIONS The cor. of secs. 30 and 31 on the W. bdy. and the $\frac{1}{4}$ sec. cor. of Secs. 30 and 31 are iron posts with a brass cap as set and described in the official record. Dears · vittod The original location monuments are substantial mounds of stone with posts. Sur. No. 1555, Pittman lode, Cor. No. 3 is a stone properly set an marked. Cor. No. 4 is missing, having been destroyed by road excavation. The bearing rock was found for this cor. Line 3-4 was found to be N. 11° 21' E., 1472.46 ft. instead of N. 11° 30' E., 1500.0 ft. as approved. Lines 2-3 and 4-1 are shown as approved. . Too mon . FIELD ASSISTANT ron Gor. Raymond W. White, Chainman A swart, the conter of which bears 7. 82 300 W., 150 ft. from Tr. A. 1, Wer Frage #3 lede, shaft 727210 ft. weep, cared. A più, tre center of which bears N. Sh" Go! .. . 137 Tt. 1 on Cor. World No. 1, Mrw Sreup #3 lode, pit oxfold ft. desg, daved. A show, the cauter of which hears S. 80° 201 M., 115 ft. from Cor-No.1, New Group #3 lode, shalt hebrel ft. deep, caved. Value, \$300. A ghill, the center of valet beers 2. 5% 30% w. The co. 30. I, for troup #3 Lode, about blandered balads cs. co. 2. Value, "coo. The district very start of the let droup (1 look, the center of the shuff the bring the discovery point, is an the lone line S. T. 23' W., 10.0 To. Link J-1, suelt there is deep . M.L. DIAT A pit, the danter of slaws bears A. G. 15' W., 100 it. from Cor. 5 016 A shelt, ith request of which bears ". 40" 30" E., no ft. Cer. 70. 1, Yes Group & lode, staff harm 30 th. 2000, cav blue, 13:5. Kabalt, the quater of which bears M. Fit add W., 65 ft. No. 1, Med amond the lede, shalt laborar ft. Gives, cared. Walter, they was the control of the control water. Hit, the conter of which hears W. 73' not be, 132 Mt. 129 tor. Mr. I, No Whom the lade, pix Court it deer, maryd.

5878 ··

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

CERTIFICATE OF SURVEYOR

Sept. 15, 1960
I, J.WITTIAM WAARA
Mineral Surveyor, hereby certify upon honor that in pursuance of an order received from the
office Cadastral Engineer ,at Phoenix Arizona.
dated, I have faithfully and correctly executed the survey of
the mining claim of Roy Cornett ,
known as the New Group #1, New Group #2, New Group #3 and New Group #4 lodes
(Lode, placer, or mill site) situate in Cherry Creek Mining District, Yavapai County, Arizona.
T. 14 N. , R. 3 E. , G.& S.R. Meridian, Arizona, and
designated as Survey No4530, which is represented in the foregoing field notes as having been
executed by me and under my direction, and that said survey has been made in strict conformity with said order, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes, and I do further certify that the labor expended and improvements made
upon or for the benefit of the lodes location(s) embraced in the said mining claim by
claimant(s) orhis grantors are fully stated in my report therein, and that the character, extent, location, and itemized value thereof are specified therein with particularity and full detail, and that no portion of, or interest in, said labor and improvements so credited to this claim has been included in the estimate of expenditures upon any other claim.
Marilla 1
Prescott Arizona. (Place) (Mineral Surveyor)
CERTIFICATE OF APPROVAL
Bureau of Land Management, Survey Office
Phoenix, Arizona June 8 , 19 61
(Place) (Date)
The foregoing field notes of mineral survey No. 4530, in Cherry Creek Mining District
Secs. 30 & 31 , T. 14 N. , R. 3 E. , Gila & Salt River Meridian,
Arizona , executed by, Mineral Surveyor, (State)
under order dated 6-1-60; Amd. 12-1-60, having been critically examined and the necessary corrections made prior to their certification by the surveyor, the field notes and the survey therein described are hereby approved.
Fred J. Weiler
State Director
(Title)
CERTIFICATE OF TRANSCRIPT
I CERTIFY that the foregoing transcript of field notes of the above described mineral survey No

(Title)

CEPARTMENT OF THE INTERIOR CEPARTMENT OF THE INTERIOR CURRENU OF LAND MANN GEMENT

CERTIFICATE OF FURVEYOR

Make at Surveyor, hereby on My upon bones that in purcussion of an ordered from the
The state of the s
to verses set becomes appeared but glimbilish send I
tongwel my the live to well all the companies of the description of the first base of the companies of the c
The same in the state of the same of the s
the control of the co
designated as Survey No. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.
chimintys) or
The second secon
SAVORISA TO STADRIGUE
Ling to the state of the state
The contract of the contract o
The receptor had edge of the summer No. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.
The received at a second of the second of th
The receptor had edge of the summer No. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.
The locations have solve of this and authors Woulder in the second State
The coregans lade rotes of mineral nurvey No. 1.22. in
The foregoing field rotes of this rai survey We. 1.2.2. In
The coregans lade rotes of mineral nurvey No. 1.22. in